


## assembly instructions

Family: Cambridge | Item No. 4640 / 4642

## **Drawing 1 - Fixture Mounting**



## Vstart here


- 1. Find a clear area in which you can work.
- 2. Unpack fixture and glass from carton.
- 3. Carefully review instructions prior to assembly.

\*\*\* The construction of this fixture will be accomplished by first assembling the main body, installing the mounting hardware, making all necessary electrical connections, hanging the fixture and then completing final assembly.

**SAFETY WARNING: READ WIRING AND GROUNDING INSTRUCTIONS (I.S. 18)** AND ANY ADDITIONAL DIRECTIONS. TURN POWER SUPPLY OFF DURING INSTALLATION. IF NEW WIRING IS REQUIRED, CONSULT A QUALIFIED **ELECTRICIAN OR LOCAL AUTHORITIES FOR CODE REQUIREMENTS.** 

- 1. Prepare mounting strap (A) by threading the two long mounting screws (B) into the back of the universal strap - see Drawing 1.
- Be sure the holes into which the screws are threaded match the spacing of holes (D) in the back plate (E).
- 2. Attach mounting strap (A) to junction box (J) using two 1" screws (C) NOT provided.

## **Drawing 3 - Glass Installation**



- Make electrical connections from supply wire to fixture lead wires. Refer to instruction sheet (I.S. 18) and follow all instructions to make all necessary wiring connections. Then refer back to this sheet to continue installation of this fixture.
- 1. To mount fixture, slip the two mounting screws (B) through the two mounting holes (D) in the backplate (E) - see Drawing 1.
- 2. While holding fixture in place, thread the two ball knobs (F) on to the end of the mounting screws (B), and tighten.
- 1. To install glass (2) first slip candle sleeve (1) over socket (S) See Drawing 3.
- 2. Now, slip small hole in bottom of glass (2) over candle sleeve (1).
- 3. To complete assembly, slip candle chaser (3) over top of candle sleeve (1).
- 4. Fixture can now be lamped accordingly.