


Bulbs: 60W CAND. G 16½

ASSEMBLY INSTRUCTIONS

[DRAWING 1]



[DRAWING 2]

- 1 To assemble main body, slip center tube **(b)** along wire and thread into nipple **(c)** located at the top of the main body assembly **(a)** - *See Drawing 2*.
- 2 Slip outer tubing **(d)** over center tube **(b)** followed by cap **(e)**.
- 3 Slip loop **(f)** along wire and thread onto top of center tube **(b)** and tighten.
- 4 Rotate arms **(k)** until they are approximately 72 degrees apart - *See Drawing 1*.

[illegible]

- 1 To install shade, remove socket ring (1) from socket (2)- See Drawing 2.
- 2 Slip shade (3) over socket (2) and hold in position.
- 3 Thread socket ring (1) onto socket (2) and hand-tighten to secure shade.
- 4 Fixture can now be lamped accordingly.

This Prosecco semi-flush uses 4 sizes of crystal pendalogues.

- 1 Working from the top of the fixture down, attach medium crystal pendants (2) to eyelets (g) - See Drawing 2.
- 2 Attach large crystal pendants (3) to eyelets (h).
- 3 Attach small crystal pendants (1) to eyelets (i).
- 3 Attach extra large crystal pendant (4) to eyelet (j).

R

800.421.3517 WWW.FREDRICKRAMOND.COM
1.26.09